



CLIMATISEUR MOBILE ÉLECTRONIQUE - ECRAN LED

MOBILE AIR CONDITIONER - LED DISPLAY

THCLI125E (Non réversible chaud-froid / Without heat pump model)

THCLI125ER (Réversible chaud-froid / Heat pump model)



Double affichage
Double display



Réversible chaud-froid
Heat pump model



Programmation : 24h
Timer: 24h



Clavier LED
LED display



Télécommande
Remote control



Ventilation : 3 vitesses
3 speeds wind



Panneau de ventilation orientable
Adjustable grid



FR

- ▶ Puissance réfrigérante : 12000 Btu / h (3,5 kW)
- ▶ Puissance absorbée : 1345 W
- ▶ Niveau sonore : 65 dB
- ▶ Panneau de ventilation orientable haut et bas
- ▶ Ventilation : 3 vitesses
- ▶ Programmation : 24h
- ▶ Déshumidification : 28.8 L / jour
- ▶ Débit d'air : 340 m³ / h
- ▶ Réversible chaud-froid - THCLI125ER
- ▶ Puissance chauffante : 2.9Kw - THCLI125ER
- ▶ Puissance absorbée : 1391W - THCLI125ER

EN

- ▶ Cooling capacity: 12000Btu / h (3,5 kW)
- ▶ Power consumption: 1345W
- ▶ Noise level: 65 dB
- ▶ Adjustable grid up and down
- ▶ 3 speeds wind
- ▶ Timer: 24h
- ▶ Dehumidify: 28.8L / day
- ▶ Air flow: 340m³ / h
- ▶ Heat pump model - THCLI125ER
- ▶ Heating capacity: 2.9Kw - THCLI125ER
- ▶ Power heat consumption: 1391W - THCLI125ER

Ref.	Gencod	Dimensions (cm)	Qty/40'HC
THCLI125E	3527570066597	44 x 33,5 x 71,5	440pcs
THCLI125ER	3527570066603	44 x 33,5 x 71,5	440pcs

Classe énergétique / Class: A

Certification: CE / ROHS

Réfrigérant / Gaz: R290

Surface pièce préconisée / Room area: 20 - 25 m²